



CoreLine Downlight – The clear choice for LED

CoreLine Downlight

The CoreLine Downlight range of recessed luminaires is designed to replace CFL-ni/CFL-i based downlight luminaires. Their attractive TCO helps customers to make the switch to LED. These luminaires create a natural lighting effect for use in general lighting applications. They also deliver instant energy savings and have a much longer lifetime, creating a real value-for-money and environmentally friendly solution. They are easy to install thanks to their standard cut-out size and push-in connectors.

Benefits

- Reduced operating costs thanks to energy saving and longer lifetime
- One-to-one replacement, facilitating the switch from conventional to LED luminaires
- Suitable for professional applications thanks to DALI dimming and aluminum reflector

Features

- Available in 1100 and 2100 lumen versions
- Energy-efficient: up to 100 lm/W
- DALI version available
- Choice of color temperature: 3000 and 4000 K
- Protected glass available as an option (also enables IP44 protection)

Application

- General lighting in corridors
- Retail stores
- Reception areas
- Indoor circulation areas

CoreLine Downlight

Specifications

Type	DN130B (version with white reflector) DN131B (version with aluminum reflector)
Ceiling type	Plaster (board) ceiling
Light source	Non replaceable LED module
Power	11 W (1100 lm) 22 W (2100 lm)
Efficacy	Up to 100 lm/W
Luminous flux	1100 lm 2100 lm
Correlated Color	3000 K (Warm white)
Temperature	4000 K (Neutral white)
Color Rendering Index	80
Median useful life	50,000 hours
L70B50	
Median useful life	30,000 hours
L80B50	
Median useful life	15,000 hours
L90B50	
Driver failure rate	1.5% per 5000 hours
Average ambient temperature	+25 °C

Operating temperature range	-10 to +40 °C
Driver	Built-in External, with DALI interface
Mains voltage	230 or 240 V / 50-60 Hz
Dimming	DALI dimmable Not dimmable
Controls system input	DALI
Material	Housing: plastic Reflector: plastic
Color	DN130B: white reflector / white rim DN131B: aluminium reflector / white rim
Optic	Reflector, white / aluminum
Connection	Push-in connector with pull relief
Installation	Fixation by spring fasteners Through-wiring possible (not for DALI version)
Accessories	Protected glass also creating IP44
Remarks	DALI version has external driver

Versions



CoreLine Downlight

-	
Driver failure rate at 5,000 hours	1 %
Application Conditions	
Suitable for random switching	Yes
Approval and Application	
Mech. impact protection code	IK02
Operating and Electrical	
Input Voltage	220-240 V
General Information	
Beam angle of light source	120 °
CE mark	CE mark
Protection class IEC	Safety class I (I)
Driver included	Yes
ENEC mark	-
Flammability mark	F
Glow-wire test	850/5
Light source replaceable	No
Number of gear units	1 unit
Initial Performance (IEC Compliant)	
Init. Colour rendering index	≥80
Luminous flux tolerance	+/-10%
Mechanical and Housing	
Colour	White RAL 9003

Application Conditions

Order Code	Full Product Name	Ambient temperature range	Maximum dimming level
32580400	DN140B LED10S/830 PSU WR PI6	-20 to +40 °C	Not applicable
32581100	DN140B LED10S/840 PSU WR PI6	-20 to +40 °C	Not applicable
32582800	DN140B LED10S/830 PSD-E WR	-20 to +40 °C	1%
32583500	DN140B LED10S/840 PSD-E WR	-20 to +40 °C	1%
32831700	DN140B LED10S/830 PSD-E WR ELB3	0 to +35 °C	1%
32832400	DN140B LED10S/840 PSD-E WR ELB3	0 to +35 °C	1%
32584200	DN140B LED20S/830 PSU WR PI6	-20 to +40 °C	Not applicable
32585900	DN140B LED20S/840 PSU WR PI6	-20 to +40 °C	Not applicable
32586600	DN140B LED20S/830 PSD-E WR	-20 to +40 °C	1%
32587300	DN140B LED20S/840 PSD-E WR	-20 to +40 °C	1%
32833100	DN140B LED20S/830 PSD-E WR ELB3	0 to +35 °C	1%
32834800	DN140B LED20S/840 PSD-E WR ELB3	0 to +35 °C	1%
32588000	DN140B LED10S/830 PSU C PI6	-20 to +40 °C	Not applicable
32589700	DN140B LED10S/840 PSU C PI6	-20 to +40 °C	Not applicable
32590300	DN140B LED10S/830 PSD-E C	-20 to +40 °C	1%
32591000	DN140B LED10S/840 PSD-E C	-20 to +40 °C	1%
32835500	DN140B LED10S/830 PSD-E C ELB3	0 to +35 °C	1%
32836200	DN140B LED10S/840 PSD-E C ELB3	0 to +35 °C	1%
32592700	DN140B LED20S/830 PSU C PI6	-20 to +40 °C	Not applicable
32593400	DN140B LED20S/840 PSU C PI6	-20 to +40 °C	Not applicable
32594100	DN140B LED20S/830 PSD-E C	-20 to +40 °C	1%
32595800	DN140B LED20S/840 PSD-E C	-20 to +40 °C	1%
32837900	DN140B LED20S/830 PSD-E C ELB3	0 to +35 °C	1%
32838600	DN140B LED20S/840 PSD-E C ELB3	0 to +35 °C	1%
32596500	DN140B LED10S/830 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32597200	DN140B LED10S/840 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32598900	DN140B LED10S/830 PSD-E WR IP54	-20 to +40 °C	1%
32599600	DN140B LED10S/840 PSD-E WR IP54	-20 to +40 °C	1%
32600900	DN140B LED20S/830 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32601600	DN140B LED20S/840 PSU WR IP54 PI6	-20 to +40 °C	Not applicable
32602300	DN140B LED20S/830 PSD-E WR IP54	-20 to +40 °C	1%
32603000	DN140B LED20S/840 PSD-E WR IP54	-20 to +40 °C	1%
32604700	DN140B LED10S/830 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32605400	DN140B LED10S/840 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32606100	DN140B LED10S/830 PSD-E C IP54	-20 to +40 °C	1%
32607800	DN140B LED10S/840 PSD-E C IP54	-20 to +40 °C	1%
32608500	DN140B LED20S/830 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32609200	DN140B LED20S/840 PSU C IP54 PI6	-20 to +40 °C	Not applicable
32610800	DN140B LED20S/830 PSD-E C IP54	-20 to +40 °C	1%
32611500	DN140B LED20S/840 PSD-E C IP54	-20 to +40 °C	1%

Approval and Application

Order Code	Full Product Name	Ingress protection code	Order Code	Full Product Name	Ingress protection code
32580400	DN140B LED10S/830 PSU WR PI6	IP20	32584200	DN140B LED20S/830 PSU WR PI6	IP20
32581100	DN140B LED10S/840 PSU WR PI6	IP20	32585900	DN140B LED20S/840 PSU WR PI6	IP20
32582800	DN140B LED10S/830 PSD-E WR	IP20	32586600	DN140B LED20S/830 PSD-E WR	IP20
32583500	DN140B LED10S/840 PSD-E WR	IP20	32587300	DN140B LED20S/840 PSD-E WR	IP20
32831700	DN140B LED10S/830 PSD-E WR ELB3	IP20	32833100	DN140B LED20S/830 PSD-E WR ELB3	IP20
32832400	DN140B LED10S/840 PSD-E WR ELB3	IP20	32834800	DN140B LED20S/840 PSD-E WR ELB3	IP20

CoreLine Downlight

Order Code	Full Product Name	Ingress protection code
32588000	DN140B LED10S/830 PSU C PI6	IP20
32589700	DN140B LED10S/840 PSU C PI6	IP20
32590300	DN140B LED10S/830 PSD-E C	IP20
32591000	DN140B LED10S/840 PSD-E C	IP20
32835500	DN140B LED10S/830 PSD-E C ELB3	IP20
32836200	DN140B LED10S/840 PSD-E C ELB3	IP20
32592700	DN140B LED20S/830 PSU C PI6	IP20
32593400	DN140B LED20S/840 PSU C PI6	IP20
32594100	DN140B LED20S/830 PSD-E C	IP20
32595800	DN140B LED20S/840 PSD-E C	IP20
32837900	DN140B LED20S/830 PSD-E C ELB3	IP20
32838600	DN140B LED20S/840 PSD-E C ELB3	IP20
32596500	DN140B LED10S/830 PSU WR IP54 PI6	IP20/54
32597200	DN140B LED10S/840 PSU WR IP54 PI6	IP20/54

Order Code	Full Product Name	Ingress protection code
32598900	DN140B LED10S/830 PSD-E WR IP54	IP20/54
32599600	DN140B LED10S/840 PSD-E WR IP54	IP20/54
32600900	DN140B LED20S/830 PSU WR IP54 PI6	IP20/54
32601600	DN140B LED20S/840 PSU WR IP54 PI6	IP20/54
32602300	DN140B LED20S/830 PSD-E WR IP54	IP20/54
32603000	DN140B LED20S/840 PSD-E WR IP54	IP20/54
32604700	DN140B LED10S/830 PSU C IP54 PI6	IP20/54
32605400	DN140B LED10S/840 PSU C IP54 PI6	IP20/54
32606100	DN140B LED10S/830 PSD-E C IP54	IP20/54
32607800	DN140B LED10S/840 PSD-E C IP54	IP20/54
32608500	DN140B LED20S/830 PSU C IP54 PI6	IP20/54
32609200	DN140B LED20S/840 PSU C IP54 PI6	IP20/54
32610800	DN140B LED20S/830 PSD-E C IP54	IP20/54
32611500	DN140B LED20S/840 PSD-E C IP54	IP20/54

Controls and Dimming

Order Code	Full Product Name	Dimmable
32580400	DN140B LED10S/830 PSU WR PI6	No
32581100	DN140B LED10S/840 PSU WR PI6	No
32582800	DN140B LED10S/830 PSD-E WR	Yes
32583500	DN140B LED10S/840 PSD-E WR	Yes
32831700	DN140B LED10S/830 PSD-E WR ELB3	Yes
32832400	DN140B LED10S/840 PSD-E WR ELB3	Yes
32584200	DN140B LED20S/830 PSU WR PI6	No
32585900	DN140B LED20S/840 PSU WR PI6	No
32586600	DN140B LED20S/830 PSD-E WR	Yes
32587300	DN140B LED20S/840 PSD-E WR	Yes
32833100	DN140B LED20S/830 PSD-E WR ELB3	Yes
32834800	DN140B LED20S/840 PSD-E WR ELB3	Yes
32588000	DN140B LED10S/830 PSU C PI6	No
32589700	DN140B LED10S/840 PSU C PI6	No
32590300	DN140B LED10S/830 PSD-E C	Yes
32591000	DN140B LED10S/840 PSD-E C	Yes
32835500	DN140B LED10S/830 PSD-E C ELB3	Yes
32836200	DN140B LED10S/840 PSD-E C ELB3	Yes
32592700	DN140B LED20S/830 PSU C PI6	No
32593400	DN140B LED20S/840 PSU C PI6	No

Order Code	Full Product Name	Dimmable
32594100	DN140B LED20S/830 PSD-E C	Yes
32595800	DN140B LED20S/840 PSD-E C	Yes
32837900	DN140B LED20S/830 PSD-E C ELB3	Yes
32838600	DN140B LED20S/840 PSD-E C ELB3	Yes
32596500	DN140B LED10S/830 PSU WR IP54 PI6	No
32597200	DN140B LED10S/840 PSU WR IP54 PI6	No
32598900	DN140B LED10S/830 PSD-E WR IP54	Yes
32599600	DN140B LED10S/840 PSD-E WR IP54	Yes
32600900	DN140B LED20S/830 PSU WR IP54 PI6	No
32601600	DN140B LED20S/840 PSU WR IP54 PI6	No
32602300	DN140B LED20S/830 PSD-E WR IP54	Yes
32603000	DN140B LED20S/840 PSD-E WR IP54	Yes
32604700	DN140B LED10S/830 PSU C IP54 PI6	No
32605400	DN140B LED10S/840 PSU C IP54 PI6	No
32606100	DN140B LED10S/830 PSD-E C IP54	Yes
32607800	DN140B LED10S/840 PSD-E C IP54	Yes
32608500	DN140B LED20S/830 PSU C IP54 PI6	No
32609200	DN140B LED20S/840 PSU C IP54 PI6	No
32610800	DN140B LED20S/830 PSD-E C IP54	Yes
32611500	DN140B LED20S/840 PSD-E C IP54	Yes

General Information

Order Code	Full Product Name	Optic type	Product family code
32580400	DN140B LED10S/830 PSU WR PI6	WR	-
32581100	DN140B LED10S/840 PSU WR PI6	WR	-
32582800	DN140B LED10S/830 PSD-E WR	WR	DN140B
32583500	DN140B LED10S/840 PSD-E WR	WR	DN140B
32831700	DN140B LED10S/830 PSD-E WR ELB3	WR	DN140B
32832400	DN140B LED10S/840 PSD-E WR ELB3	WR	DN140B
32584200	DN140B LED20S/830 PSU WR PI6	WR	-
32585900	DN140B LED20S/840 PSU WR PI6	WR	-
32586600	DN140B LED20S/830 PSD-E WR	WR	DN140B

Order Code	Full Product Name	Optic type	Product family code
32587300	DN140B LED20S/840 PSD-E WR	WR	DN140B
32833100	DN140B LED20S/830 PSD-E WR ELB3	WR	DN140B
32834800	DN140B LED20S/840 PSD-E WR ELB3	WR	DN140B
32588000	DN140B LED10S/830 PSU C PI6	C	-
32589700	DN140B LED10S/840 PSU C PI6	C	-
32590300	DN140B LED10S/830 PSD-E C	C	DN140B
32591000	DN140B LED10S/840 PSD-E C	C	DN140B
32835500	DN140B LED10S/830 PSD-E C ELB3	C	DN140B
32836200	DN140B LED10S/840 PSD-E C ELB3	C	DN140B

CoreLine Downlight

Order Code	Full Product Name	Optic type	Product family code
32592700	DN140B LED20S/830 PSU C PI6	C	-
32593400	DN140B LED20S/840 PSU C PI6	C	-
32594100	DN140B LED20S/830 PSD-E C	C	DN140B
32595800	DN140B LED20S/840 PSD-E C	C	DN140B
32837900	DN140B LED20S/830 PSD-E C ELB3	C	DN140B
32838600	DN140B LED20S/840 PSD-E C ELB3	C	DN140B
32596500	DN140B LED10S/830 PSU WR IP54 PI6	WR	-
32597200	DN140B LED10S/840 PSU WR IP54 PI6	WR	-
32598900	DN140B LED10S/830 PSD-E WR IP54	WR	DN140B
32599600	DN140B LED10S/840 PSD-E WR IP54	WR	DN140B
32600900	DN140B LED20S/830 PSU WR IP54 PI6	WR	-

Order Code	Full Product Name	Optic type	Product family code
32601600	DN140B LED20S/840 PSU WR IP54 PI6	WR	-
32602300	DN140B LED20S/830 PSD-E WR IP54	WR	DN140B
32603000	DN140B LED20S/840 PSD-E WR IP54	WR	DN140B
32604700	DN140B LED10S/830 PSU C IP54 PI6	C	-
32605400	DN140B LED10S/840 PSU C IP54 PI6	C	-
32606100	DN140B LED10S/830 PSD-E C IP54	C	DN140B
32607800	DN140B LED10S/840 PSD-E C IP54	C	DN140B
32608500	DN140B LED20S/830 PSU C IP54 PI6	C	-
32609200	DN140B LED20S/840 PSU C IP54 PI6	C	-
32610800	DN140B LED20S/830 PSD-E C IP54	C	DN140B
32611500	DN140B LED20S/840 PSD-E C IP54	C	DN140B

Initial Performance (IEC Compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
32580400	DN140B LED10S/830 PSU WR PI6	(0.435,0.405)	3000 K	116 lm/W	1100 lm
32581100	DN140B LED10S/840 PSU WR PI6	(0.381,0.379)	4000 K	116 lm/W	1100 lm
32582800	DN140B LED10S/830 PSD-E WR	(0.435,0.405)	3000 K	96 lm/W	1100 lm
32583500	DN140B LED10S/840 PSD-E WR	(0.381,0.379)	4000 K	96 lm/W	1100 lm
32831700	DN140B LED10S/830 PSD-E WR ELB3	(0.435,0.405)	3000 K	76 lm/W	1100 lm
32832400	DN140B LED10S/840 PSD-E WR ELB3	(0.381,0.379)	4000 K	76 lm/W	1100 lm
32584200	DN140B LED20S/830 PSU WR PI6	(0.435,0.404)	3000 K	116 lm/W	2200 lm
32585900	DN140B LED20S/840 PSU WR PI6	(0.380,0.377)	4000 K	116 lm/W	2200 lm
32586600	DN140B LED20S/830 PSD-E WR	(0.435,0.404)	3000 K	107 lm/W	2200 lm
32587300	DN140B LED20S/840 PSD-E WR	(0.380,0.377)	4000 K	107 lm/W	2200 lm
32833100	DN140B LED20S/830	(0.435,0.404)	3000 K	94 lm/W	2200 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
	PSD-E WR ELB3				
32834800	DN140B LED20S/840 PSD-E WR ELB3	(0.380,0.377)	4000 K	94 lm/W	2200 lm
32588000	DN140B LED10S/830 PSU C PI6	(0.433,0.405)	3000 K	116 lm/W	1100 lm
32589700	DN140B LED10S/840 PSU C PI6	(0.379,0.379)	4000 K	116 lm/W	1100 lm
32590300	DN140B LED10S/830 PSD-E C	(0.433,0.405)	3000 K	96 lm/W	1100 lm
32591000	DN140B LED10S/840 PSD-E C	(0.379,0.379)	4000 K	96 lm/W	1100 lm
32835500	DN140B LED10S/830 PSD-E C ELB3	(0.433,0.405)	3000 K	76 lm/W	1100 lm
32836200	DN140B LED10S/840 PSD-E C ELB3	(0.379,0.379)	4000 K	76 lm/W	1100 lm
32592700	DN140B LED20S/830 PSU C PI6	(0.432,0.404)	3000 K	116 lm/W	2200 lm
32593400	DN140B LED20S/840 PSU C PI6	(0.378,0.377)	4000 K	116 lm/W	2200 lm
32594100	DN140B LED20S/830 PSD-E C	(0.432,0.404)	3000 K	107 lm/W	2200 lm

CoreLine Downlight

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
32595800	DN140B LED20S/840 PSD-E C	(0.378,0.377)	4000 K	107 lm/W	2200 lm
32837900	DN140B LED20S/830 PSD-E C ELB3	(0.432,0.404)	3000 K	94 lm/W	2200 lm
32838600	DN140B LED20S/840 PSD-E C ELB3	(0.378,0.377)	4000 K	94 lm/W	2200 lm
32596500	DN140B LED10S/830 PSU WR IP54 PI6	(0.435,0.405)	3000 K	116 lm/W	1100 lm
32597200	DN140B LED10S/840 PSU WR IP54 PI6	(0.381,0.379)	4000 K	116 lm/W	1100 lm
32598900	DN140B LED10S/830 PSD-E WR IP54	(0.435,0.405)	3000 K	96 lm/W	1100 lm
32599600	DN140B LED10S/840 PSD-E WR IP54	(0.381,0.379)	4000 K	96 lm/W	1100 lm
32600900	DN140B LED20S/830 PSU WR IP54 PI6	(0.435,0.404)	3000 K	116 lm/W	2200 lm
32601600	DN140B LED20S/840	(0.380,0.377)	4000 K	116 lm/W	2200 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
	PSU WR IP54 PI6				
32602300	DN140B LED20S/830 PSD-E WR IP54	(0.435,0.404)	3000 K	107 lm/W	2200 lm
32603000	DN140B LED20S/840 PSD-E WR IP54	(0.380,0.377)	4000 K	107 lm/W	2200 lm
32604700	DN140B LED10S/830 PSU C IP54 PI6	(0.433,0.405)	3000 K	116 lm/W	1100 lm
32605400	DN140B LED10S/840 PSU C IP54 PI6	(0.379,0.379)	4000 K	116 lm/W	1100 lm
32606100	DN140B LED10S/830 PSD-E C IP54	(0.433,0.405)	3000 K	96 lm/W	1100 lm
32607800	DN140B LED10S/840 PSD-E C IP54	(0.379,0.379)	4000 K	96 lm/W	1100 lm
32608500	DN140B LED20S/830 PSU C IP54 PI6	(0.432,0.404)	3000 K	116 lm/W	2200 lm
32609200	DN140B LED20S/840 PSU C IP54 PI6	(0.378,0.377)	4000 K	116 lm/W	2200 lm
32610800	DN140B LED20S/830 PSD-E C IP54	(0.432,0.404)	3000 K	107 lm/W	2200 lm
32611500	DN140B LED20S/840 PSD-E C IP54	(0.378,0.377)	4000 K	107 lm/W	2200 lm

Initial Performance (IEC Compliant) (2/2)

Order Code	Full Product Name	Initial input power
32580400	DN140B LED10S/830 PSU WR PI6	9.5 W
32581100	DN140B LED10S/840 PSU WR PI6	9.5 W
32582800	DN140B LED10S/830 PSD-E WR	11.5 W
32583500	DN140B LED10S/840 PSD-E WR	11.5 W
32831700	DN140B LED10S/830 PSD-E WR ELB3	14.5 W
32832400	DN140B LED10S/840 PSD-E WR ELB3	14.5 W
32584200	DN140B LED20S/830 PSU WR PI6	19 W
32585900	DN140B LED20S/840 PSU WR PI6	19 W
32586600	DN140B LED20S/830 PSD-E WR	20.5 W
32587300	DN140B LED20S/840 PSD-E WR	20.5 W
32833100	DN140B LED20S/830 PSD-E WR ELB3	23.5 W
32834800	DN140B LED20S/840 PSD-E WR ELB3	23.5 W

Order Code	Full Product Name	Initial input power
32588000	DN140B LED10S/830 PSU C PI6	9.5 W
32589700	DN140B LED10S/840 PSU C PI6	9.5 W
32590300	DN140B LED10S/830 PSD-E C	11.5 W
32591000	DN140B LED10S/840 PSD-E C	11.5 W
32835500	DN140B LED10S/830 PSD-E C ELB3	14.5 W
32836200	DN140B LED10S/840 PSD-E C ELB3	14.5 W
32592700	DN140B LED20S/830 PSU C PI6	19 W
32593400	DN140B LED20S/840 PSU C PI6	19 W
32594100	DN140B LED20S/830 PSD-E C	20.5 W
32595800	DN140B LED20S/840 PSD-E C	20.5 W
32837900	DN140B LED20S/830 PSD-E C ELB3	23.5 W
32838600	DN140B LED20S/840 PSD-E C ELB3	23.5 W

CoreLine Downlight

Order Code	Full Product Name	Initial input power
32596500	DN140B LED10S/830 PSU WR IP54 PI6	9.5 W
32597200	DN140B LED10S/840 PSU WR IP54 PI6	9.5 W
32598900	DN140B LED10S/830 PSD-E WR IP54	11.5 W
32599600	DN140B LED10S/840 PSD-E WR IP54	11.5 W
32600900	DN140B LED20S/830 PSU WR IP54 PI6	19 W
32601600	DN140B LED20S/840 PSU WR IP54 PI6	19 W
32602300	DN140B LED20S/830 PSD-E WR IP54	20.5 W
32603000	DN140B LED20S/840 PSD-E WR IP54	20.5 W

Order Code	Full Product Name	Initial input power
32604700	DN140B LED10S/830 PSU C IP54 PI6	9.5 W
32605400	DN140B LED10S/840 PSU C IP54 PI6	9.5 W
32606100	DN140B LED10S/830 PSD-E C IP54	11.5 W
32607800	DN140B LED10S/840 PSD-E C IP54	11.5 W
32608500	DN140B LED20S/830 PSU C IP54 PI6	19 W
32609200	DN140B LED20S/840 PSU C IP54 PI6	19 W
32610800	DN140B LED20S/830 PSD-E C IP54	20.5 W
32611500	DN140B LED20S/840 PSD-E C IP54	20.5 W

