



# LuxSpace recessed – high efficiency, visual comfort and a stylish design

## LuxSpace Mini, recessed

Customers are looking to optimize all their resources, and that means not just their running costs (energy, etc.) but also their human resources. Energy savings are therefore a priority, but they must not have an adverse effect on the well-being of employees, who need a pleasant environment in order to be more productive, or on customers, who want to enjoy their shopping experience. LuxSpace provides the perfect combination of efficiency, light comfort and design, without compromising on lighting performance (color rendering and color uniformity). It offers a wide choice of options for creating the desired ambience, no matter the application.

### Benefits

- Best-in-class efficacy
- Creates a gentle, natural light, ensuring visual comfort
- Perfect integration with the ceiling thanks to the thin, narrow rim; rimless version ideal for integration into plaster ceilings

## LuxSpace Mini, recessed

### Features

- Choice of four optics: high-gloss, faceted, matt and white
- Heights: deep (up to UGR 19), low (up to UGR 22)
- Rim colors: high-gloss metalized, white (RAL9010), grey, black (RAL9004) as standard (any other RAL color possible upon request)
- Rimless version available
- Surface-mounted version available
- Compliant for central emergency lighting with DC
- Multiple additional options: PG and PGO (IP54 front face), emergency lighting (single battery 3 hours), suspended deco glasses, through-wiring

### Application

- Offices
- Retail
- Hospitals
- Hotels
- Airports

### Specifications

<b>Type</b>	DN560B (low height recessed version) DN561B (deep recessed version)
<b>Ceiling type</b>	Plaster (board) ceiling
<b>Light source</b>	Non replaceable LED module
<b>Power</b>	8 or 11.2 W (depending on configuration)
<b>Luminous flux</b>	780 to 1200 lm (depending on configuration)
<b>Correlated Color Temperature</b>	2700, 3000 or 4000 K
<b>Color Rendering Index</b>	> 80 90 (available in 3000 K)
<b>Median useful life L70B50</b>	70,000 hours
<b>Median useful life L80B50</b>	50,000 hours
<b>Median useful life L90B50</b>	25,000 hours
<b>Average ambient temperature</b>	25 °C
<b>Operating temperature range</b>	+10 to +40 °C
<b>Driver</b>	Separate

<b>Mains voltage</b>	230 or 240 V / 50-60 Hz
<b>Dimming</b>	DALI dimming possible (PSED-E)
<b>Options</b>	Emergency lighting 3 hours (EL3) Protection glass (PG or PGO, IP54 front face) Through-wiring Rimless version for plaster ceiling Suspended glasses: opal (SG-O), frosted circle (SG-FRC) and frosted halo ring (SG-HR-FR) External or plug-in 3-pole Wieland/Adels connector
<b>Material</b>	Housing and rim: aluminum Reflector: plastic, aluminum coated (for high-gloss and faceted optics)
<b>Color</b>	Rim: white (RAL 9010), grey (similar to RAL 9006), black (RAL 9005) or high-gloss metalized
<b>Optic</b>	High-gloss mirror (C) Matt mirror (M) Faceted reflector (F) White reflector (WR)
<b>Connection</b>	Push-in connector or with pull relief
<b>Installation</b>	Fixation by means of spring fasteners
<b>Remarks</b>	External driver included

# LuxSpace Mini, recessed

## Versions



LuxSpace2 Mini Low height  
recessed - LED Module, system  
flux 1200 lm



LuxSpace2 Mini Deeprecessed -  
LED Module, system flux 1200 lm

### Application Conditions

Ambient temperature range	+10 to +25 °C
Suitable for random switching	Yes

### Approval and Application

Mech. impact protection code	IK02
------------------------------	------

### Operating and Electrical

Input Voltage	220 to 240 V
---------------	--------------

### General Information

CE mark	CE mark
Protection class IEC	Safety class II (II)
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	F
Glow-wire test	850/5
Light source replaceable	No
Number of gear units	1 unit
Optic type	C

### Initial Performance (IEC Compliant)

Init. Colour rendering index	>80
Luminous flux tolerance	+/-10%

### Mechanical and Housing

Colour	White RAL 9003
--------	----------------

### Application Conditions

Order Code	Full Product Name	Maximum dimming level
97036900	DN560B LED8S/830 PSU-E C WH	-
97037600	DN560B LED8S/840 PSU-E C WH	-
97040600	DN560B LED8S/830 DIA-VLC-E C WH	1%
97041300	DN560B LED8S/840 DIA-VLC-E C WH	1%
97044400	DN560B LED12S/830 PSU-E C WH	-
97045100	DN560B LED12S/840 PSU-E C WH	-
97046800	DN560B LED12S/830 PSU-E C PG WH	-
97047500	DN560B LED12S/840 PSU-E C PG WH	-
97050500	DN560B LED12S/830 PSU-E C ELP3 WH	-
97051200	DN560B LED12S/840 PSU-E C ELP3 WH	-
97052900	DN560B LED12S/830 DIA-VLC-E C WH	1%
97053600	DN560B LED12S/840 DIA-VLC-E C WH	1%
97056700	DN560B LED20S/830 PSU-E C WH	-
97057400	DN560B LED20S/840 PSU-E C WH	-
97038300	DN561B LED8S/830 PSU-E C WH	-
97039000	DN561B LED8S/840 PSU-E C WH	-
97042000	DN561B LED8S/830 DIA-VLC-E C WH	1%
97043700	DN561B LED8S/840 DIA-VLC-E C WH	1%
97048200	DN561B LED12S/830 PSU-E C WH	-
97049900	DN561B LED12S/840 PSU-E C WH	-
97055000	DN561B LED12S/840 DIA-VLC-E C WH	1%

## Approval and Application

Order Code	Full Product Name	Ingress protection code
97036900	DN560B LED8S/830 PSU-E C WH	IP20
97037600	DN560B LED8S/840 PSU-E C WH	IP20
97040600	DN560B LED8S/830 DIA-VLC-E C WH	IP20
97041300	DN560B LED8S/840 DIA-VLC-E C WH	IP20
97044400	DN560B LED12S/830 PSU-E C WH	IP20
97045100	DN560B LED12S/840 PSU-E C WH	IP20
97046800	DN560B LED12S/830 PSU-E C PG WH	IP54/20
97047500	DN560B LED12S/840 PSU-E C PG WH	IP54/20

Order Code	Full Product Name	Ingress protection code
97050500	DN560B LED12S/830 PSU-E C ELP3 WH	IP20
97051200	DN560B LED12S/840 PSU-E C ELP3 WH	IP20
97052900	DN560B LED12S/830 DIA-VLC-E C WH	IP20
97053600	DN560B LED12S/840 DIA-VLC-E C WH	IP20
97056700	DN560B LED20S/830 PSU-E C WH	IP20
97057400	DN560B LED20S/840 PSU-E C WH	IP20
97038300	DN561B LED8S/830 PSU-E C WH	IP20
97039000	DN561B LED8S/840 PSU-E C WH	IP20

## LuxSpace Mini, recessed

Order Code	Full Product Name	Ingress protection code
97042000	DN561B LED8S/830 DIA-VLC-E C WH	IP20
97043700	DN561B LED8S/840 DIA-VLC-E C WH	IP20
97048200	DN561B LED12S/830 PSU-E C WH	IP20

Order Code	Full Product Name	Ingress protection code
97049900	DN561B LED12S/840 PSU-E C WH	IP20
97055000	DN561B LED12S/840 DIA-VLC-E C WH	IP20

### Controls and Dimming

Order Code	Full Product Name	Dimmable
97036900	DN560B LED8S/830 PSU-E C WH	No
97037600	DN560B LED8S/840 PSU-E C WH	No
97040600	DN560B LED8S/830 DIA-VLC-E C WH	Yes
97041300	DN560B LED8S/840 DIA-VLC-E C WH	Yes
97044400	DN560B LED12S/830 PSU-E C WH	No
97045100	DN560B LED12S/840 PSU-E C WH	Yes
97046800	DN560B LED12S/830 PSU-E C PG WH	No
97047500	DN560B LED12S/840 PSU-E C PG WH	No
97050500	DN560B LED12S/830 PSU-E C ELP3 WH	No
97051200	DN560B LED12S/840 PSU-E C ELP3 WH	No
97052900	DN560B LED12S/830 DIA-VLC-E C WH	Yes

Order Code	Full Product Name	Dimmable
97053600	DN560B LED12S/840 DIA-VLC-E C WH	Yes
97056700	DN560B LED20S/830 PSU-E C WH	No
97057400	DN560B LED20S/840 PSU-E C WH	No
97038300	DN561B LED8S/830 PSU-E C WH	No
97039000	DN561B LED8S/840 PSU-E C WH	No
97042000	DN561B LED8S/830 DIA-VLC-E C WH	Yes
97043700	DN561B LED8S/840 DIA-VLC-E C WH	Yes
97048200	DN561B LED12S/830 PSU-E C WH	No
97049900	DN561B LED12S/840 PSU-E C WH	No
97055000	DN561B LED12S/840 DIA-VLC-E C WH	Yes

### General Information

Order Code	Full Product Name	Product family code
97036900	DN560B LED8S/830 PSU-E C WH	DN560B
97037600	DN560B LED8S/840 PSU-E C WH	DN560B
97040600	DN560B LED8S/830 DIA-VLC-E C WH	DN560B
97041300	DN560B LED8S/840 DIA-VLC-E C WH	DN560B
97044400	DN560B LED12S/830 PSU-E C WH	DN560B
97045100	DN560B LED12S/840 PSU-E C WH	DN560B
97046800	DN560B LED12S/830 PSU-E C PG WH	DN560B
97047500	DN560B LED12S/840 PSU-E C PG WH	DN560B
97050500	DN560B LED12S/830 PSU-E C ELP3 WH	DN560B
97051200	DN560B LED12S/840 PSU-E C ELP3 WH	DN560B
97052900	DN560B LED12S/830 DIA-VLC-E C WH	DN560B

Order Code	Full Product Name	Product family code
97053600	DN560B LED12S/840 DIA-VLC-E C WH	DN560B
97056700	DN560B LED20S/830 PSU-E C WH	DN560B
97057400	DN560B LED20S/840 PSU-E C WH	DN560B
97038300	DN561B LED8S/830 PSU-E C WH	DN561B
97039000	DN561B LED8S/840 PSU-E C WH	DN561B
97042000	DN561B LED8S/830 DIA-VLC-E C WH	DN561B
97043700	DN561B LED8S/840 DIA-VLC-E C WH	DN561B
97048200	DN561B LED12S/830 PSU-E C WH	DN561B
97049900	DN561B LED12S/840 PSU-E C WH	DN561B
97055000	DN561B LED12S/840 DIA-VLC-E C WH	DN561B

### Initial Performance (IEC Compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
97036900	DN560B LED8S/830 PSU-E C WH	(0.43, 0.40) SDCM <2	3000 K	131 lm/W	840 lm
97037600	DN560B LED8S/840 PSU-E C WH	(0.38, 0.38) SDCM <2	4000 K	140 lm/W	840 lm
97040600	DN560B LED8S/830 DIA-VLC-E C WH	(0.43, 0.40) SDCM <2	3000 K	131 lm/W	840 lm
97041300	DN560B LED8S/840 DIA-VLC-E C WH	(0.38, 0.38) SDCM <2	4000 K	140 lm/W	840 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
97044400	DN560B LED12S/830 PSU-E C WH	(0.43, 0.40) SDCM <2	3000 K	127 lm/W	1350 lm
97045100	DN560B LED12S/840 PSU-E C WH	(0.38, 0.38) SDCM <2	4000 K	138 lm/W	1350 lm
97046800	DN560B LED12S/830 PSU-E C PG WH	(0.43, 0.40) SDCM <2	3000 K	127 lm/W	1350 lm

## LuxSpace Mini, recessed

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
97047500	DN560B LED12S/840 PSU-E C PG WH	(0.38, 0.38)	4000 K	138 lm/W	1350 lm
97050500	DN560B LED12S/830 PSU-E C ELP3 WH	(0.43, 0.40)	3000 K	99 lm/W	1350 lm
97051200	DN560B LED12S/840 PSU-E C ELP3 WH	(0.38, 0.38)	4000 K	105 lm/W	1350 lm
97052900	DN560B LED12S/830 DIA-VLC-E C WH	(0.43, 0.40)	3000 K	127 lm/W	1350 lm
97053600	DN560B LED12S/840 DIA-VLC-E C WH	(0.38, 0.38)	4000 K	138 lm/W	1350 lm
97056700	DN560B LED20S/830 PSU-E C WH	(0.43, 0.40)	3000 K	121 lm/W	2200 lm
97057400	DN560B LED20S/840 PSU-E C WH	(0.38, 0.38)	4000 K	134 lm/W	2200 lm

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Colour Temperature	Initial LED luminaire efficacy	Initial luminous flux
97038300	DN561B LED8S/830 PSU-E C WH	(0.43, 0.40)	3000 K	131 lm/W	840 lm
97039000	DN561B LED8S/840 PSU-E C WH	(0.38, 0.38)	4000 K	140 lm/W	840 lm
97042000	DN561B LED8S/830 DIA-VLC-E C WH	(0.43, 0.40)	3000 K	131 lm/W	840 lm
97043700	DN561B LED8S/840 DIA-VLC-E C WH	(0.38, 0.38)	4000 K	140 lm/W	840 lm
97048200	DN561B LED12S/830 PSU-E C WH	(0.43, 0.40)	3000 K	127 lm/W	1350 lm
97049900	DN561B LED12S/840 PSU-E C WH	(0.38, 0.38)	4000 K	138 lm/W	1350 lm
97055000	DN561B LED12S/840 DIA-VLC-E C WH	(0.38, 0.38)	4000 K	138 lm/W	1350 lm

### Initial Performance (IEC Compliant) (2/2)

Order Code	Full Product Name	Initial input power
97036900	DN560B LED8S/830 PSU-E C WH	6.4 W
97037600	DN560B LED8S/840 PSU-E C WH	6 W
97040600	DN560B LED8S/830 DIA-VLC-E C WH	6.4 W
97041300	DN560B LED8S/840 DIA-VLC-E C WH	6 W
97044400	DN560B LED12S/830 PSU-E C WH	10.6 W
97045100	DN560B LED12S/840 PSU-E C WH	9.8 W
97046800	DN560B LED12S/830 PSU-E C PG WH	10.6 W
97047500	DN560B LED12S/840 PSU-E C PG WH	9.8 W
97050500	DN560B LED12S/830 PSU-E C ELP3 WH	13.6 W
97051200	DN560B LED12S/840 PSU-E C ELP3 WH	12.8 W
97052900	DN560B LED12S/830 DIA-VLC-E C WH	10.6 W

Order Code	Full Product Name	Initial input power
97053600	DN560B LED12S/840 DIA-VLC-E C WH	9.8 W
97056700	DN560B LED20S/830 PSU-E C WH	18.2 W
97057400	DN560B LED20S/840 PSU-E C WH	16.4 W
97038300	DN561B LED8S/830 PSU-E C WH	6.4 W
97039000	DN561B LED8S/840 PSU-E C WH	6 W
97042000	DN561B LED8S/830 DIA-VLC-E C WH	6.4 W
97043700	DN561B LED8S/840 DIA-VLC-E C WH	6 W
97048200	DN561B LED12S/830 PSU-E C WH	10.6 W
97049900	DN561B LED12S/840 PSU-E C WH	9.8 W
97055000	DN561B LED12S/840 DIA-VLC-E C WH	9.8 W

## LuxSpace Mini, recessed

