



# CityCharm Cordoba

## BDS490 CG20-/730 II S GR CLO C6K FQQ-PX1

CityCharm Cordoba - 15 pcs - ClearGuide 2000 lm - LED - 730 warm white - Power supply unit regulating with constant light output - 220 to 240 V - 50 to 60 Hz - Safety class II (II) - Symmetrical - Polycarbonate bowl/cover - Gray - - - Constant light output - - - Luminaire surge protection level up to 6 kV differential mode and 8 kV common mode - Cable 6.0 m without plug - 35 °C - Spigot for diameter 60 mm

CityCharm Cordoba is designed for use in urban areas where comfortable lighting, ambiance and design play an important role. Its unobtrusive appearance makes it a timeless, future-proof luminaire that is ideal for residential areas, parks, footpaths and cycle lanes, where visual comfort and maximum efficiency are key. CityCharm offers a choice of two iconic designs (Cordoba and Cone) and various accessories, enabling you to create a lighting solution that carries your signature, both by day and by night. CityCharm luminaires are also available as a complete set, with a choice of dedicated poles and brackets.

### Product data

General Information			
Number of light sources	15 [ 15 pcs]	Driver included	Yes
Lamp family code	CG20 [ ClearGuide 2000 lm]	Decorative spill-light	-
Light source colour	730 warm white	Optical cover/lens type	PC [ Polycarbonate bowl/cover]
Light source replaceable	Yes	Luminaire light beam spread	360°
Number of gear units	1 unit	Embedded control	CLO [ Constant light output]
Gear	EB [ Electronic]	Control interface	-
Driver/power unit/transformer	PSR-CLO [ Power supply unit regulating with constant light output]	Connection	Flying leads/wires
		Cable	Cable 6.0 m without plug
		Protection class IEC	Safety class II (II)

## CityCharm Cordoba

Coating	-
Glow-wire test	650/5 [ Temperature 650 °C, duration 5 s]
Flammability mark	NO [ -]
CE mark	CE mark
ENEC mark	ENEC mark
UL mark	-
Warranty period	5 years
Optic type outdoor	Symmetrical
Photocell	No [ -]
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Constant light output	Yes
Spare parts available	Yes
Number of products on MCB (16 A type B)	32
Lifecycle services	Maintenance services
Photobiological risk	Photobiological risk group 1 @ 200mm to EN62471
Product recyclability	95%
EU RoHS compliant	Yes
WEEE mark	-
Light source engine type	LED
Accessory PFC	-
Serviceability class	Class A, the luminaire is equipped with serviceable parts (when applicable): LED board, driver, control units, surge-protection device, optics, front cover and mechanical parts
Product family code	BDS490 [ CityCharm Cordoba]

### Light Technical

Upward light output ratio	0.03
Scotopic/photopic lumen ratio	1.24
Initial luminous flux at 15 °C	2004 lm
Initial luminous flux at 25 °C	2004 lm
Initial luminous flux at 35 °C	2004 lm
Standard tilt angle post-top	0°
Standard tilt angle side entry	0°

### Operating and Electrical

Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Control signal voltage	-
Initial CLO power consumption	14.4 W
Average CLO power consumption	16.2 W
End CLO power consumption	18 W
Inrush current	27 A
Inrush time	15 ms
Driver current	344 mA
Power factor (max.)	0.9
Power factor (min.)	0.8

Power factor (nom.)	0.828
---------------------	-------

### Controls and Dimming

Dimmable	No
----------	----

### Mechanical and Housing

Housing material	Aluminum
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Aluminium
Mounting device	60 [ Spigot for diameter 60 mm]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Torque	25
Overall height	529 mm
Overall diameter	556 mm
Effective projected area	0.1124 m²
Colour	Gray
Dimensions (height x width x depth)	529 x NaN x NaN mm (20.8 x NaN x NaN in)

### Approval and Application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [ 20 J vandal-resistant]
Surge protection (common/differential)	Luminaire surge protection level up to 6 kV differential mode and 8 kV common mode

### Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	1696 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	94 lm/W
Init. Corr. Colour Temperature	3000 K
Init. Colour rendering index	≥70
Initial chromaticity	(0.430, 0.400) SDCM <3
Initial input power	18 W
Power consumption tolerance	+/-10%
Init. colour rendering index tolerance	+/-2

### Over Time Performance (IEC Compliant)

Lumen maintenance at median useful life* 100,000 h	L100
--	------

### Application Conditions

Ambient temperature range	-40 to +50 °C
Maximum dimming level	Not applicable

### Product Data

Full product code	871869693922200
Order product name	BDS490 CG20-/730 II S GR CLO C6K FQQ-PX1
EAN/UPC – product	8718696939222
Order code	93922200

## CityCharm Cordoba

SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	910505017427
SAP net weight (piece)	12.000 kg



### Dimensional drawing



CityCharm BDS490/491/492

