



ZXP399 DMX Controls and Accessories

ZXP399 Addressing Kit DMX

6 to 24 DC V - - Hz - Finger-protected - CE mark - Black

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar).;DMX Controls include a main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device.;Main Controller: Industrial computer that can control up to 6,000 DMX universes.;Stand-alone Controller: Fits all medium applications with up to 700 DMX universes.;Wiring accessories include leader and jump cables with male and female IP67 connectors and end-caps.;Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes.;DMX Amplifier: Compact, IP65 and low-power repeater that can amplify the DMX signal for up 100 metres.

Product data

General Information		Approval and Application	
CE mark	CE mark	Overall width	88.15 mm
Accessory colour	Black	Overall height	30 mm
		Dimensions (height x width x depth)	30 x 88 x 122 mm (1.2 x 3.5 x 4.8 in)
Operating and Electrical		Product Data	
Input Voltage	6 to 24 DC V	Full product code	911401746102
Input frequency	- Hz	Order product name	ZXP399 Addressing Kit DMX
Mechanical and Housing			
Overall length	122.4 mm		


ZXP399 DMX Controls and Accessories

Order code	01746102
SAP numerator – quantity per pack	1
Numerator – packs per outer box	72
SAP material	911401746102

SAP net weight (piece)	0.500 kg
------------------------	----------



Dimensional drawing



ZXP399

