



HID ignitors for series systems

SI 51 220-240V 50/60HZ

HID ignitors for series systems

Product data

| Operating and Electrical | |
|---------------------------|-----------------|
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| Input Voltage | 220 to 240 V |
| Wiring | |
| Connector Type | Screw |
| Temperature | |
| Ambient temperature range | -20 °C to 75 °C |
| T-Case Maximum (Max) | 80 °C |
| Mechanical and Housing | |
| Housing | SNI-85 |

| Approval and Application | |
|---------------------------------|-----------------------------|
| Approval Marks | CE marking ENEC certificate |
| Product Data | |
| Full product code | 871150091553530 |
| Order product name | SI 51 220-240V 50/60Hz |
| Order code | 91553530 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 48 |
| Material Nr. (12NC) | 913619519966 |
| Full product name | SI 51 220-240V 50/60Hz |
| EAN/UPC - Case | 8711500908353 |

HID ignitors for series systems

Dimensional drawing

☰

| Product | D1 | C1 | A1 | A2 | B1 |
|------------------------|--------|---------|---------|---------|---------|
| SI 51 220-240V 50/60Hz | 4.3 mm | 38.0 mm | 84.5 mm | 65.0 mm | 41.0 mm |

