



HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

BSN400L301I 220V 60HZ

The HID Basic Semi-Parallel ballast is an impregnated (HID standard) electromagnetic copper/iron ballast for use with an external ignitor for HID lamps.

Product data

General Information		Temperature	
Application code	L301 I	T-winding (max.)	130 °C
		Delta-T normal conditions	65 °C
Operating and Electrical		Approval and Application	
Input Voltage	220 V	Approval marks	CE marking
Input frequency	60 Hz		
Power factor 100% load (min.)	0.85	Product Data	
Mains voltage performance (AC)	-8% - +6%	Full product code	871016303473730
Mains voltage safety (AC)	-10% - +10%	Order product name	BSN 400L 301I
Input current with PF correction	2.4 A	EAN/UPC – product	8710163148830
Input current without PF Correction	4.45 A	Order code	03473730
Power factor without PF compensation (nom.)	0.45	SAP numerator – quantity per pack	1
Power losses (nom.)	25.5 W	Numerator – packs per outer box	4
		SAP material	913710102950
Wiring		SAP net weight (piece)	4.300 kg
Connector type	Screw		
System characteristics			
Rated ballast-lamp power	400 W		

HID-Basic Semi-Parallel ballasts for SON/CDM/MH lamps

Dimensional drawing



Product	D1	C1	A1	A2	B1
BSN 400L 301I	6.2 mm	82 mm	165.0 mm	150 mm	96.5 mm

BSN 400 L301 I

