



# Actinic BL TL(-K)/TL-D(-K)

## Actinic BL TL 11W/10

With an optimized spectrum matching the eye sensitivity of the housefly, Actinic BL TL(-K)/TL-D(-K)/TL-E/PL-S and PL-L lamps are perfect for attracting insects. They have virtually no UV-B output, and so are perfectly safe. What's more, with the lowest mercury content in the industry and being 100% lead-free, these lamps represent a very good environmental choice. Furthermore, the availability of a wide range of form factors (straight (T5, T8, T12), circular (TL-E) and compact (PL-S/PL-L)) and wattages enables you to make all kinds of designs for your electronic fly killers.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General Information		UV Depreciation at 2,000 h	
Cap base	G5 [ G5]		45 %
Main application	Insect traps	Operating and Electrical	
Useful life (nom.)	2000 h	Power (Rated) (Nom)	11.5 W
		Lamp current (nom.)	0.400 A
Light Technical		Voltage (Nom)	34 V
Colour Code	10	Mechanical and Housing	
Colour designation	Actinic	Bulb shape	T16
Chromaticity coordinate X (nom.)	230	Approval and Application	
Chromaticity coordinate Y (nom.)	230	Mercury (Hg) content (nom.)	4.4 mg
Depreciation at 500 Hours	30 %		
UV depreciation at 1,000 h	40 %		

# Actinic BL TL(-K)/TL-D(-K)

UV	
UV-B/UV-A (IEC)	0.2 %
UV-A radiation 100 hours (IEC)	2.0 W
Product Data	
Full product code	871150095145827
Order product name	Actinic BL TL 11W/10
EAN/UPC – product	8711500951458

Order code	95145827
SAP numerator – quantity per pack	1
Numerator – packs per outer box	250
SAP material	928000601030
SAP net weight (piece)	21.000 g


## Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
Actinic BL TL 11W/10	16 mm	212.1 mm	219.2 mm	216.8 mm	226.3 mm

TL 11W/10

## Photometric data



XDPB\_XUVATL\_10-Spectral power distribution B/W



XDPO\_XUVATL\_10-Spectral power distribution Colour

