



# MASTERCcolour CDM-TC Elite

## MASTERCcolour CDM-TC Elite 70W/930 G8.5 1CT/12

Compact, single-ended, very high-efficiency, long-life ceramic metal-halide discharge lamp producing crisp white sparkling light with high color rendering

### Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures
- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General information		Colour designation	
Cap base	G8.5 [ G8.5]	Colour designation	Warm White (WW)
Operating position	UNIVERSAL [ Any or Universal (U)]	Lumen maintenance 12,000 hours (nom.)	82 %
Life to 5% failures (nom.)	12000 h	Lumen maintenance 10,000 hours (nom.)	83 %
Life to 10% failures (nom.)	14000 h	Lumen maintenance 2,000 hours (nom.)	95 %
Life to 20% failures (nom.)	16000 h	Lumen maintenance 5,000 hours (nom.)	88 %
Life to 50% failures (nom.)	20000 h	Chromaticity coordinate X (nom.)	0.435
ANSI code HID	C139/E	Chromaticity coordinate Y (nom.)	0.396
		Correlated Colour Temperature (Nom)	3000 K
		Luminous efficacy (rated) (nom.)	107 lm/W
		Colour-rendering index (min.)	87
		Colour rendering index (nom.)	90
Light technical			
Colour Code	930 [ CCT of 3,000 K]		
Luminous flux (rated) (nom.)	7800 lm		

# MASTERC colour CDM-TC Elite

## Operating and electrical

Power (Rated) (Nom)	73.2 W
Lamp current run-up (max.)	2 A
Ignition supply voltage (max.)	198 V
Ignition peak voltage (max.)	5000 V
Ignition supply voltage (min.)	198 V
Re-ignition time (min.) (max.)	15 min
Ignition time (max.)	30 s
Voltage (Max)	90 V
Voltage (Min)	80 V
Voltage (Nom)	85 V

## Controls and dimming

Dimmable	No
Run-up time 90% (max.)	3 min
Run-up time 90% (nom.)	1.5 min

## Mechanical and housing

Lamp Finish	Clear
Bulb shape	T14 [ T 14 mm]

## Approval and application

Mercury (Hg) content (nom.)	6.6 mg
Energy consumption kWh/1,000 hours	80 kWh

## UV

PET (NIOSH) (min.)	8 h/500lx
Damage factor D/fc (max.)	0.3

## Luminaire design requirements

Bulb temperature (max.)	550 °C
Pinch temperature (max.)	350 °C
Pinch Temperature (Max)-DUP(do not use)	350 °C

## Product data

Full product code	871869648471500
Order product name	MASTERC colour CDM-TC Elite 70W/930 G8.5 1CT/12
EAN/UPC – product	8718696484715
Order code	48471500
SAP numerator – quantity per pack	1
Local code description	MASTERC CDM-TC ELITE 70W/930 G8.5 1CT/12
Numerator – packs per outer box	12
SAP material	928189505129
Net Weight (Piece)	10.000 g
ILCOS code	MT/UB-70/930-H-G8.5-17/85

## Dimensional drawing


D

Product	D (max)	O	L (min)	L (max)	L	C (max)
MASTERC colour CDM-TC	15 mm	7.15	51 mm	53 mm	52 mm	85 mm
Elite 70W/930 G8.5 1CT/12		mm				


MASTERC colour CDM-TC Elite 70W/930 G8.5 1CT/12

# MASTERCoulour CDM-TC Elite

## Photometric data



## Lifetime



LDLE\_CDMTC-E\_0002-Life expectancy diagram

