



GreenSpace Accent Projector – A flexible and affordable all-rounder for retail applications

GreenSpace Accent Projector

Thanks to the GreenSpace Accent family, retailers and building operators can enjoy the superior quality of light and market-leading energy-efficiency of PerfectAccent optics for a reasonable initial investment. The new PerfectAccent optics also provide sparkle on the merchandise and improve shopper eye comfort. The GreenSpace Accent Projector can seamlessly integrate with 3C- and DALI-tracks, Coreline Trunking and Maxos fusion. Installation and repositioning are quick and easy and require no additional tools. For fashion and food retailers, the GreenSpace Accent Projector is available with special LED flavours and Fresh food LED recipes to show the merchandise in the very best light. Check out our Fashion and Food catalogue pages to find out more about PremiumWhite, PremiumColor, Fresh Meat, Rosé, Frost and Champagne.

Benefits

- Clean, robust and neutral design
- Increased sparkle and shopper eye comfort with PerfectAccent optics
- High energy-efficiency, maintained over the full lifetime of the product

GreenSpace Accent Projector

Features

- Toolless installation and repositioning on Track (ST321T), Coreline trunking (ST321Y; a double spotlight version) or Maxos fusion (ST321S)
- Available with a high flux up to 4,900 lm, a wide range of optics, optional front glass and barndoor accessories
- Retail LED flavours and fresh food LED recipes included
- Very broad aiming flexibility, including upward lighting
- Available for normal mains (PSU), simple DALI dimming (PSD), Interact compatible DALI (DIA) and indoor positioning (DIA-VLC)

Application

- Retail

Warnings and Safety

- All photometrical data is calculated without optional front glass. Flux should be reduced by 3.5% when using a front glass
- Cleaning of the optic is only allowed with pressurised air. Touching the LED or reflector is forbidden. For food preparation areas and areas with high levels of dust, the use of the optional front glass is strongly advised, as it can be cleaned with a (dry) microfibre cloth.
- During manipulation and/or maintenance, the product has to be switched off and cooled down
- The product must be installed out of arm's reach. Manipulating the product when hot is only possible with an insulated glove

Versions

GREENSPACE ACCENT MAXOS
FUSION GEN2 - 24°



Product details



ST321T - GreenSpace Accent
Projector back view white



ST321T - GreenSpace Accent
Projector RPO plastic white

GreenSpace Accent Projector

Product details



ST321Y - GreenSpace Accent
Projector Coreline trunking
connect

Application Conditions

Ambient temperature range	+10 to +40 °C
Maximum dimming level	Not applicable
Suitable for random switching	Not applicable

Approval and Application

Mech. impact protection code	IK02
Ingress protection code	IP20

Controls and Dimming

Dimmable	No
----------	----

Operating and Electrical

Input Voltage	220 to 240 V
---------------	--------------

General Information

Beam angle of light source	120 °
CE mark	CE mark
Protection class IEC	Safety class II (II)
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	NO
Glow-wire test	650/30
Light source replaceable	No
Number of gear units	2 units
Optic type	WB
Product family code	ST321Y

Initial Performance (IEC Compliant)

Initial chromaticity	(0.38, 0.38) SDCM<3
Init. Corr. Colour Temperature	4000 K
Init. Colour rendering index	≥80
Luminous flux tolerance	+/-10%

Mechanical and Housing

Colour	White
--------	-------

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
97496100	ST321Y LED27S/840 PSU WB WH	115 lm/W	2700 lm	23.5 W
97499200	ST321Y LED39S/840 PSU WB WH	139 lm/W	3900 lm	28 W

GreenSpace Accent Projector

