



Xitanium LED linear drivers – isolated

Xitanium 25W 0.5/0.6A 42V 13 230V

Xitanium isolated drivers are ideal for professional low voltage (LV) linear office systems. The isolated drivers are available in DALI dimmable and programmable, 1-10V dimmable, fixed output and single current versions. They offer ease of design-in and make the approbation process simpler. The DALI drivers and new fixed output drivers feature SimpleSet technology, low output current ripple of 4% for high and low frequencies and low standby specifications. The low output current ripple ensures no interference with security-, cell phone- or web cameras and scanners.

Product data

General Information			
Nominal lifetime	50,000 hour(s)	Inrush Current Peak (Max)	18 A
Lighting Technology	LED	Output Power (Max)	25 W
		Default output current	500 mA
		Inrush Current Width to 50% of Peak	240 µs
		Power Factor 100% Load (Max)	0
		Energy Metering	No
		Constant Current (CC)	True
		Constant Voltage (CV)	False
		Diagnostics	False
		Output Power (Min)	15 W
		Output Current (Min)	500 mA
		Output Voltage (Max)	42 V
		Output Voltage (Min)	30 V
		Number of Products on MCB (16A Type-C) (Max)	28 piece/unit
		Wiring	
		Connector Type Input Terminals	Wago 744

Xtitanium LED linear drivers – isolated

Hot Wiring	no
Connector Type Output Terminals	Wago 744
Output Wire Cross Section (Max)	1.5 mm ²
Output Wire Cross Section (Min)	0.5 mm ²
Cable Length From Device to Lamp	0.6 m
Input Wire Gauge	16-20
Input wire strip length	8 mm to 9 mm mm
Input Wire Cross Section (Max)	1.5 mm ²
Input Wire Cross Section (Min)	0.5 mm ²
Output wire strip length	8 mm to 9 mm mm

System characteristics

Central DC Operation	No
YellowDot ready	No

Temperature

Ambient temperature range	-20 °C to 50 °C
T-Case Lifetime (Max)	75 °C
T-Case Maximum (Max)	75 °C
Module Temperature Protection	no
Maximum case temperature (in case of failure)	110 °C

Controls and Dimming

Dimmable	No
D4i compliant	No
DynaDimmer	No
Constant light output	No

Mechanical and Housing

Product Length	250 mm
Housing	Linear 350x48.6x13 3p3p

Overall length	250 mm
Overall width	48.6 mm
Overall height	13 mm
Dimensions (Height x Width x Depth)	13 x 49 x 250 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Isolation Classification	SELV
Short Circuit Protection	Protected
Over Power Protection	Protected
Open Circuit Protection	Protected
Approval Marks	CCC certificate CE marking ENEC certificate RCM compliance REACH compliance RoHS compliance
Corridor Mode	True
Output Current Set Options	Manual
Protection class IEC	Safety class I

Product Data

Full product code	694793914481500
Order product name	Xtitanium 25W 0.5/0.6A 42V 13 230V
Order code	14481500
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	929001425380
Full product name	Xtitanium 25W 0.5/0.6A 42V 13 230V
EAN/UPC - Case	6947939144822
EAN/UPC - Product/Case	6947939144815

