

PHILIPS

Lighting



Xitanium LED linear drivers – non-isolated

Xitanium 35W 0.08-0.35A 150V 16 230V

Xitanium linear non-isolated drivers are ideal for high voltage (HV) professional general lighting applications. The range includes DALI dimmable and programmable, 1-10V dimmable, non-dimmable and single current versions. They offer high efficiency, good quality of light and full flexibility. The new generation of 16mm DALI drivers offer ultimate performance. They comply with the latest DiiA standards, including implementation of the new DALI parts related to data. Configuring the drivers can be done quickly and wirelessly with SimpleSet. The new 21mm DALI drivers offer the best value for money.

Product data

General Information		Protection Level Up (LN-Earth) at 5 kA (Max)	
Nominal lifetime	100,000 hour(s)	2 kV	
Lighting Technology	LED	Input current (AC)	0.17 mA
Operating and Electrical		Input current (DC)	0.17
Line Frequency	50 to 60 Hz	Inrush Current Peak (Max)	15.3 A
Input Frequency	50 to 60 Hz	Output Power (Max)	35 W
Mains voltage operation (DC)	168-275 V	Default output current	80 mA
Total Harmonic Distortion IEC (Max)	20 %	Inrush Current Width to 50% of Peak	221 µs
Output Current Ripple (Max)	4 %	Power Factor 100% Load (Max)	0.9
Maximum Efficiency at Full Load	90 %	Energy Metering	No
Output Current (Max)	350 mA	Constant Current (CC)	True
Output Current Tolerance (Max)	5 %	Constant Voltage (CV)	False
Mains voltage performance (DC)	186-250 V	Diagnostics	True
Power Factor (Fraction)	0.9	Output Power (Min)	10 W
Open Circuit Voltage (DC) (Max)	250 V	Output Current (Min)	80 mA
Protection Level Up (L-N) at 5 kA (Max)	1 kV	Output Voltage (Max)	150 V
		Output Voltage (Min)	50 V

Xtanium LED linear drivers – non-isolated

Number of Products on MCB (16A Type-C) (Max)	37 piece/unit
--	---------------

Wiring

Connector Type Input Terminals	Wago 744
Hot Wiring	no
Connector Type Output Terminals	Wago 744
Output Wire Cross Section (Max)	1.5 mm ²
Output Wire Cross Section (Min)	0.5 mm ²
Cable Length From Device to Lamp	2 m
Input Wire Gauge	16-20
Input wire strip length	8 mm to 9 mm mm
Input Wire Cross Section (Max)	1.5 mm ²
Input Wire Cross Section (Min)	0.5 mm ²
Output wire strip length	8 mm to 9 mm mm

System characteristics

Central DC Operation	Yes
YellowDot ready	No

Temperature

Ambient temperature range	-25 °C to 50 °C
T-Case Lifetime (Max)	65 °C
T-Case Maximum (Max)	75 °C
Module Temperature Protection	no
Maximum case temperature (in case of failure)	110 °C

Controls and Dimming

Dimmable	No
D4i compliant	No
DynaDimmer	No
Constant light output	No

Mechanical and Housing

Product Length	280 mm
Housing	Office 280x30x16 4p4p
Overall length	280 mm
Overall width	30 mm
Overall height	16 mm
Dimensions (Height x Width x Depth)	16 x 30 x 280 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Isolation Classification	No
Short Circuit Protection	Protected
Over Power Protection	Protected
Open Circuit Protection	Protected
Approval Marks	CCC certificate CE marking ENEC certificate RCM compliance REACH compliance RoHS compliance
Corridor Mode	True
Output Current Set Options	LEDset
Protection class IEC	Safety class I

Product Data

Full product code	871869670593300
Order product name	Xtanium 35W 0.08-0.35A 150V 16 230V
Order code	70593300
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	929001557606
Full product name	Xtanium 35W 0.08-0.35A 150V 16 230V
EAN/UPC - Case	8718696705940

