

# PHILIPS

## Lighting



# Xitanium LED downlight and spotlight drivers

## Xitanium 32W/m 0.7A 46V SC 230V

Xitanium LED drivers are leading the way in terms of reliability

### Product data

#### General Information

Lighting Technology LED

#### Operating and Electrical

Output Current Ripple (Max) 4 %  
Output Current (Max) 700 mA  
Open Circuit Voltage (DC) (Max) 60 V  
Output Power (Max) 32.2 W  
Output Power (Min) 21.7 W  
Output Current (Min) 700 mA  
Output Voltage (Max) 46 V  
Output Voltage (Min) 31 V

#### System characteristics

Central DC Operation No  
YellowDot ready No

#### Temperature

T-Case Lifetime (Max) 75 °C  
T-Case Maximum (Max) 75 °C

#### Controls and Dimming

Dimmable No

#### Mechanical and Housing

Product Length 97 mm  
Housing Mini 97x43x30 2p2p  
Overall length 97.2 mm  
Overall width 43 mm  
Overall height 30 mm  
Dimensions (Height x Width x Depth) 30 x 43 x 97 mm

#### Approval and Application

Ingress protection code IP20 [Finger-protected]  
Isolation Classification Class I and Class II  
Approval Marks CE marking CB Certificate ENEC certificate CCC certificate RCM compliance  
Output Current Set Options Preset Current  
Protection class IEC Safety class I/II

#### Product Data

Full product code 871869970223600

## Xitanium LED downlight and spotlight drivers

<b>Order product name</b>	Xitanium 32W/m 0.7A 46V SC 230V
<b>Order code</b>	70223600
<b>Numerator - Quantity Per Pack</b>	1
<b>Numerator - Packs per outer box</b>	50
<b>Material Nr. (12NC)</b>	929002105106

<b>Full product name</b>	Xitanium 32W/m 0.7A 46V SC 230V
<b>EAN/UPC - Case</b>	8718699702243

