

PHILIPS

Lighting



Xitanium LED downlight and spotlight drivers

Xitanium 10W/m 0.35A 30V SC 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information

Lighting Technology LED

Operating and Electrical

Output Current Ripple (Max) 4 %
Output Current (Max) 350 mA
Open Circuit Voltage (DC) (Max) 60 V
Output Power (Max) 10.5 W
Output Power (Min) 7 W
Output Current (Min) 350 mA
Output Voltage (Max) 30 V
Output Voltage (Min) 20 V

System characteristics

Central DC Operation No
YellowDot ready No

Temperature

T-Case Lifetime (Max) 75 °C
T-Case Maximum (Max) 75 °C

Controls and Dimming

Dimmable No

Mechanical and Housing

Product Length 97 mm
Housing Mini 97x43x30 2p2p
Overall length 97.2 mm
Overall width 43 mm
Overall height 30 mm
Dimensions (Height x Width x Depth) 30 x 43 x 97 mm

Approval and Application

Ingress protection code IP20 [Finger-protected]
Isolation Classification Class I and Class II
Approval Marks CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options Preset Current
Protection class IEC Safety class I/II

Product Data

Full product code 871869970211300

Xitanium LED downlight and spotlight drivers

Order product name	Xitanium 10W/m 0.35A 30V SC 230V
Order code	70211300
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	929002113106

Full product name	Xitanium 10W/m 0.35A 30V SC 230V
EAN/UPC - Case	8718699702120

