

PHILIPS

Lighting



Xitanium LED downlight and spotlight drivers

Xitanium 21W/m 0.7A 30V SC 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information

Lighting Technology	LED
---------------------	-----

Operating and Electrical

Output Current Ripple (Max)	4 %
Output Current (Max)	700 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	21 W
Output Power (Min)	14 W
Output Current (Min)	700 mA
Output Voltage (Max)	30 V
Output Voltage (Min)	20 V

System characteristics

Central DC Operation	No
YellowDot ready	No

Temperature

T-Case Lifetime (Max)	75 °C
T-Case Maximum (Max)	75 °C

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Product Length	97 mm
Housing	Mini 97x43x30 2p2p
Overall length	97.2 mm
Overall width	43 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 43 x 97 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	Preset Current
Protection class IEC	Safety class I/II

Product Data

Full product code	871869970215100
-------------------	-----------------

Xitanium LED downlight and spotlight drivers

Order product name	Xitanium 21W/m 0.7A 30V SC 230V
Order code	70215100
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	929002113306

Full product name	Xitanium 21W/m 0.7A 30V SC 230V
EAN/UPC - Case	8718699702168

