

# PHILIPS

## Lighting



# Xitanium LED downlight and spotlight drivers

## Xitanium 38W/m 0.9A 42V SC 230V

Xitanium LED drivers are leading the way in terms of reliability

### Product data

#### General Information

Lighting Technology	LED
---------------------	-----

#### Operating and Electrical

Output Current Ripple (Max)	4 %
Output Current (Max)	900 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	38 W
Output Power (Min)	27 W
Output Current (Min)	900 mA
Output Voltage (Max)	42 V
Output Voltage (Min)	30 V

#### System characteristics

Central DC Operation	No
YellowDot ready	No

#### Temperature

T-Case Lifetime (Max)	75 °C
T-Case Maximum (Max)	75 °C

#### Controls and Dimming

Dimmable	No
----------	----

#### Mechanical and Housing

Product Length	97 mm
Housing	Mini 97x43x30 2p2p
Overall length	97.2 mm
Overall width	43 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 43 x 97 mm

#### Approval and Application

Ingress protection code	IP20 [Finger-protected]
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	Preset Current
Protection class IEC	Safety class I/II

#### Product Data

Full product code	871869970217500
-------------------	-----------------

## Xitanium LED downlight and spotlight drivers

<b>Order product name</b>	Xitanium 38W/m 0.9A 42V SC 230V
<b>Order code</b>	70217500
<b>Numerator - Quantity Per Pack</b>	1
<b>Numerator - Packs per outer box</b>	50
<b>Material Nr. (12NC)</b>	929002113406

<b>Full product name</b>	Xitanium 38W/m 0.9A 42V SC 230V
<b>EAN/UPC - Case</b>	8718699702182

