



CorePro LEDtube EM/ Mains

CorePro LEDtube 600mm 9W 865 T8 AP I

The CorePro LEDtube is an affordable LED solution suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

Warnings and Safety

• -

Product data

General information		Operating and electrical	
Cap base	G13 [Medium Bi-Pin Fluorescent]	Input frequency	50 to 60 Hz
EU RoHS compliant	Yes	Power (Rated) (Nom)	9 W
Nominal lifetime (nom.)	30000 h	Lamp current (max.)	48 mA
Switching cycle	200000	Lamp current (min.)	48 mA
Light technical		Starting time (nom.)	0.5 s
Colour Code	865 [CCT of 6,500 K]	Warm-up time to 60% light (nom.)	0.5 s
Beam Angle (Nom)	240 °	Power factor (nom.)	0.9
Luminous flux (nom.)	900 lm	Voltage (Nom)	220-240 V
Colour designation	Cool Daylight	Temperature	
Correlated Colour Temperature (Nom)	6500 K	T-ambient (max.)	45 °C
Luminous efficacy (rated) (nom.)	100.00 lm/W	T-ambient (min.)	-20 °C
Colour consistency	<6	T storage (max.)	65 °C
Colour rendering index (nom.)	80	T storage (min.)	-40 °C
LLMF at end of nominal lifetime (nom.)	70 %	T-Case maximum (nom.)	45 °C

CorePro LEDtube EM/Mains

Controls and dimming

Dimmable	No
----------	----

Mechanical and housing

Lamp Finish	Frosted
Bulb material	Glass
Product length	600 mm
Bulb shape	Tube, double-ended


Approval and application

Energy-saving product	Yes
Approval marks	RoHS compliance CE marking KEMA Keur certificate

Product data

Full product code	871951444701100
Order product name	CorePro LEDtube 600mm 9W 865 T8 AP I
EAN/UPC – product	8719514447011
Order code	44701100
SAP numerator – quantity per pack	1
Numerator – packs per outer box	20
SAP material	929003520208
Net Weight (Piece)	0.110 kg


Dimensional drawing




CorePro LEDtube 600mm 9W 865 T8 AP I

Product	D1	D2	A1	A2	A3
CorePro LEDtube 600mm 9W 865 T8 AP I	25.7 mm	28 mm	588.5 mm	595.5 mm	602.5 mm

Photometric data




Spectral Power Distribution Colour



General uniform lighting


CorePro LEDtube EM/Mains

Photometric data





Light Distribution Diagram

Lifetime



FailureRate

LifetimeVsTc




Life Expectancy Diagram

Lumen Maintenance Diagram

CorePro LEDtube EM/Mains

Lifetime



Lumen Maintenance Diagram

