



Maxos accessories

9MX056 EC7

Electrical connector 7-pole

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Product data

General Information		Input Voltage	
Protection class IEC	Safety class I (I)	Input Voltage	220 to 240 V
Suspension accessories	No [-]	Input frequency	50 to 60 Hz
Mechanical accessories	No [-]	Circuit	No [-]
Packaging configuration	No [-]	Mechanical and Housing	
Accessory colour	-	Length	- mm
Emergency lighting accessories	No [-]	Dimensions (height x width x depth)	NaN x NaN x NaN mm (NaN x NaN x NaN in)
Product family code	9MX056 [ACC MAXOS]	Approval and Application	
Light Technical		Ingress protection code	- [-]
Optical cover/lens type accessory	No [-]	Product Data	
Operating and Electrical		Full product code	403073213179200
Electrical accessories	EC7 [Electrical connector 7-pole]	Order product name	9MX056 EC7

Maxos accessories

EAN/UPC – product	4030732131792
Order code	13179200
Numerator – quantity per pack	1
SAP numerator – packs per outer box	1
Material no. (12 NC)	910605019226

Net Weight (Piece)	0.006 kg
---------------------------	----------

