



UNIIIn-ground

BBP340 LED220/WW 3W 20D 100-240V

UNIIIn-ground family provide a complete range of up-lights in terms of wattage, beam angle and colour temperature, etc. It will make your space distinctive with more safety and convenience. Compact and robust design with a diecast aluminium housing and stainless trim, IP68 waterproof connectors ensure long-lasting operation without maintenance after installation. The waterproof connector makes installation easy and saves installation costs. As well as high-quality white light, RGB (and mono RGB) are available with a DMX512 decoder built inside. The lighting LED board can be adjusted to deliver light at precise angles to make the inspirations of lighting designers come true.

Product data

General Information	
Light source colour	730 warm white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	G [Glass]
Control interface	-
Connection	SI [Screw connection block]
Cable	Cable 0.3 m with connector 3-pole
Protection class IEC	Safety class I (I)
Flammability mark	NO [-]
CE mark	-
LED engine type	LED
Serviceability class	Class C, luminaire without serviceable parts, not serviceable

Light Technical	
Standard tilt angle post-top	-

Operating and Electrical	
Input Voltage	100 to 240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.4

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Housing material	Aluminum
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Mounting device	RMR [Recessed mounting box round]
Optical cover/lens finish	Clear
Overall height	125 mm
Overall diameter	100 mm
Colour	Steel

UNIIn-ground

Approval and Application

Ingress protection code	IP67 [Dust penetration-protected, watertight]
Mech. impact protection code	IK10 [20 J vandal-resistant]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	220 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	73 lm/W
Init. Corr. Colour Temperature	3000 K
Init. Colour rendering index	>70
Initial input power	3 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product Data

Full product code	911401755332
Order product name	BBP340 LED220/WW 3W 20D 100-240V
Order code	01755332
Numerator – quantity per pack	1
SAP numerator – packs per outer box	8
Material no. (12 NC)	911401755332
Net Weight (Piece)	0.410 kg



Dimensional drawing



Product Type	Ø, mm	H, mm
BBP340	100	140
BBP341	120	145
BBP342	140	150
BBP343	180	175
BBP344	250	185

UNIIn-ground BBP2xx/3xx/4xx

