



MSR

MSR 1200 1CT/3

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	G22 [G22]
Operating position	UNIVERSAL [Any or Universal (U)]
Main application	Studio/Disco
Life to 50% failures (nom.)	800 h
System description	Cold Strike
Light Technical	
Colour Code	- [Not Specified]
Luminous flux (min.)	96300 lm
Luminous flux (nom.)	107000 lm
Chromaticity coordinate X (nom.)	325
Chromaticity coordinate Y (nom.)	320
Correlated Colour Temperature (Nom)	5900 K
Luminous efficacy (rated) (nom.)	89 lm/W


Colour rendering index (nom.)	80
Operating and Electrical	
Power (Rated) (Nom)	1200 W
Lamp current (nom.)	13.8 A
Ignition supply voltage (min.)	207 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-base information	30x53mm
Luminaire Design Requirements	
Bulb temperature (max.)	700 °C

MSR

Pinch temperature (max.)	350 °C
Product Data	
Full product code	872790091121300
Order product name	MSR 1200 1CT/3
EAN/UPC – product	8727900911213
Order code	91121300

SAP numerator – quantity per pack	1
Numerator – packs per outer box	3
SAP material	928078105114
SAP net weight (piece)	0.150 kg

Dimensional drawing



MSR 1200

Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR 1200 1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm

Photometric data

