



MSR

MSR 575/2 10H 1CT/4

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General Information | | Operating and Electrical | |
|-------------------------------------|-----------------------------------|----------------------------------|-----------|
| Cap base | GX9.5 [GX9.5] | Luminous efficacy (rated) (nom.) | 83 lm/W |
| Operating position | UNIVERSAL [Any or Universal (U)] | Colour rendering index (nom.) | 70 |
| Main application | Studio/Disco | Power (Rated) (Nom) | 575 W |
| Life to 50% failures (nom.) | 1000 h | Lamp current (nom.) | 6.75 A |
| System description | Cold Strike | Ignition supply voltage (min.) | 207 V |
| Light Technical | | Controls and Dimming | |
| Colour Code | 2 | Dimmable | No |
| Luminous flux (min.) | 42750 lm | Mechanical and Housing | |
| Luminous flux (nom.) | 47500 lm | Cap-base information | 20mm (20) |
| Chromaticity coordinate X (nom.) | 302 | | |
| Chromaticity coordinate Y (nom.) | 320 | | |
| Correlated Colour Temperature (Nom) | 6990 K | | |
| Luminous efficacy (rated) (min.) | 75 lm/W | | |

MSR

Luminaire Design Requirements

| | |
|--------------------------|--------|
| Bulb temperature (max.) | 700 °C |
| Pinch temperature (max.) | 350 °C |

Product Data

| | |
|--------------------|---------------------|
| Full product code | 871829122127200 |
| Order product name | MSR 575/2 10H 1CT/4 |
| EAN/UPC – product | 8718291221272 |

| | |
|-----------------------------------|--------------|
| Order code | 22127200 |
| SAP numerator – quantity per pack | 1 |
| Numerator – packs per outer box | 4 |
| SAP material | 928171605115 |
| SAP net weight (piece) | 0.057 kg |

Dimensional drawing

0

| Product | D (max) | O | L (min) | L (max) | L | C (max) | F (max) | F | F (min) |
|------------------------|---------|-----------|---------|---------|----------|---------|---------|----------|---------|
| MSR 575/2 10H 1CT/4 | 30 mm | 7.0 mm | 64 mm | 66 mm | 65 mm | 125 mm | 36 mm | 35 mm | 34 mm |

MSR 575/2 10H

Photometric data

