



# MASTER LEDtube InstantFit HF T5

## Master LEDtube HF 1500mm UO 36W 865 T5

Philips MASTER LEDtube InstantFit T5 integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescents. The Philips MASTER LEDtube InstantFit T5 is the ideal solution for customers who have higher light output requirements and want to maximise value over the lifetime. The full energy savings & longer lifetime result in attractive payback times and TCO benefits.

### Product data

General Information	
Cap base	G5 [ G5]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	50000 h
Switching cycle	50,000X
Light Technical	
Colour Code	865 [ CCT of 6,500 K]
Beam Angle (Nom)	160 °
Luminous flux (nom.)	5600 lm
Colour designation	Cool Daylight
Correlated Colour Temperature (Nom)	6500 K
Luminous efficacy (rated) (nom.)	155.00 lm/W
Colour consistency	<6
Colour rendering index (nom.)	83
LLMF at end of nominal lifetime (nom.)	70 %
Operating and Electrical	
Input frequency	40000-75000 Hz

Power (Rated) (Nom)	36 W
Lamp current (max.)	750 mA
Lamp current (min.)	550 mA
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.9
Voltage (Nom)	65-75 V
Temperature	
T-ambient (max.)	45 °C
T-ambient (min.)	-20 °C
T storage (max.)	65 °C
T storage (min.)	-40 °C
T-Case maximum (nom.)	45 °C
Controls and Dimming	
Dimmable	No

# MASTER LEDtube InstantFit HF T5

## Mechanical and Housing

Lamp Finish	Frosted
Bulb material	Plastic
Product length	1500 mm


## Approval and Application

Energy efficiency label (EEL)	A++
Energy-saving product	Yes
Approval marks	RoHS compliance CE marking KEMA Keur certificate
Energy consumption kWh/1,000 hours	42 kWh

## Product Data

Full product code	871869670605300
Order product name	Master LEDtube HF 1500mm UO 36W 865 T5
EAN/UPC – product	8718696706053
Order code	70605300
Numerator – quantity per pack	1
Numerator – packs per outer box	10
SAP material	929001346302
SAP net weight (piece)	0.170 kg


## Dimensional drawing




TLED 230V 37-80W 5600lm 160D 6500K G5 ND

Product	D1	D2	A1	A2	A3
Master LEDtube HF 1500mm UO 36W 865 T5	15.2 mm	21 mm	1447.8 mm	1454.9 mm	1462 mm

## Photometric data



LEDtube 1500mm 36W G5 865 5600lm



LEDtube 1500mm 36W G5 865 5600lm



# MASTER LEDtube InstantFit HF T5

## Photometric data




LEDtube 1200mm 26W G5

## Lifetime



LEDtube 1500mm 36W G5 5600lm

LEDtube 1500mm 36W G5 5600lm




LEDtube 1500mm 36W G5 5600lm

LEDtube 1200mm 26W G5 3900lm

# MASTER LEDtube InstantFit HF T5

## Lifetime



LEDtube 1500mm 36W G5 5600lm

